

// 984AH

**Multipurpose 20 bar (300 psi)**

Tube: black synthetic elastomer.

Reinforcement: high tensile textile cords.

Cover: red synthetic elastomer with longitudinal blue stripes - abrasion, ozone and hydrocarbon resistant.

Application: compressed air, water, fuel and oil delivery in general industrial applications.

Constant operation: -10 °C +60 °C (+14 °F +140 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	13,00	0,51	20	300	60	900	48,0	1,89		0,140	0,10
8,0	5/16"	15,00	0,59	20	300	60	900	64,0	2,52		0,170	0,12
10,0	3/8"	17,00	0,67	20	300	60	900	80,0	3,15		0,200	0,14
13,0	1/2"	21,00	0,83	20	300	60	900	104,0	4,09		0,275	0,19
16,0	5/8"	25,00	0,98	20	300	60	900	128,0	5,04		0,370	0,25
19,0	3/4"	29,00	1,14	20	300	60	900	152,0	5,98		0,500	0,34
25.0	1"	35.00	1.38	20	300	60	900	200,0	7.87		0.625	0.43

102

INDUSTRIAL HOSE

// 954AH

**EVOLUTION****Multipurpose 20 bar (300 psi) - Non conductive**

Tube: black non conductive NBR.

Reinforcement: high tensile textile cords.

Cover: red NBR/PVC - abrasion, ozone and hydrocarbon resistant.

Application: premium quality compressed air, water, fuel and oil delivery in general industrial applications.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
10,0	3/8"	17,00	0,63	20	300	60	900				0,185	0,13
13,0	1/2"	21,00	0,79	20	300	60	900				0,230	0,16
19,0	3/4"	28,00	1,06	20	300	60	900				0,420	0,29
25,0	1"	35,00	1,34	20	300	60	900				0,560	0,38
32,0	1 1/4"	44,00	1,73	20	300	60	900				0,880	0,60
38,0	1 1/2"	50,00	1,97	20	300	60	900				1,020	0,69
51,0	2"	65,00	2,56	20	300	60	900				1,450	0,98